

MaxiCharger

DC Fast

60kW - 240kW



AUTEL

MaxiCharger DC Fast



Powerful

Charge faster and more efficiently

- Up to 240 kW of fast charging
- Provides up to 265 km of range in 10 min with a Maximum 400A output current
- Charging speed improved by up to 30% with boost mode



Smart Advertising and Communication Portal

Improve your ROI

- Show the charging related Info like State of Charge (SOC), Cost, kWh
- Offer an additional channel to boost revenue with the display of advertisements
- Communicate, promote or attract customers generating new revenue streams



High Reliability

Charge without worries

- Continually testing and evaluating new vehicle for interoperability
- Compatible with all vehicles of IEC standards
- Charging success rate higher than industry average

High Power meets high operability with the MaxiCharger DC Fast



Weather Resistant



21 Safety Monitoring Items



Smart Cloud Portal & OCPP Capability



Remote Update & Diagnostics



Smart Charging



Plug & Charge



96% Charging Efficiency



Flexible Hardware & Software Customization



Compatible with CCS2, CCS2 Boost or CHAdeMO



Support APP, RFID Card, Credit Card, Mobile Payment

1950 mm



820 mm

600 mm / 700 mm

*600 mm for 60-120kW, 700 mm for 140-240kW

Technical Specifications

DC Output Connection

Charging mode	Mode 4: CCS2
Output power	60kW/120kW/180kW/240kW
Output voltage	150 - 950V
Output current	CCS2: Standard: 200A; Optional 300A (Nominal), 400A (Peak) CHAdeMo: 125A or 200A
Number of outputs	2*CCS2, or 1*CCS2+1*CHAdeMO; 1*AC socket (Optional)
Peak efficiency	≥96%

AC Input Connection

Earthing system	3P, N, PE
Input voltage	3-phase 400V AC±10%
Input frequency	50Hz
Power factor	≥0.99
Harmonic distortion (THDi)	≤5%

General Characteristics

Enclosure rating	IP55; IK10
Operating altitude	2000m
Operating temperature range Storage temperature range	-35°C ~ +55°C (+50°C to +55°C with linear power de-rating) -40°C ~ +70°C
Mounting	Floor standing
Dimensions (H×W×D)	1950×820×600 mm (60kW/120kW); 1950×820×700mm (180kW/240kW)
Screen type	27 inch LCD touch screen (1920*1080)
Cable length	4.5m standard; 5.5m or 7.5m optional

User Interface

Status indication	LED / LCD / APP
User interface Connectivity	Autel Charge APP; Autel Charge Cloud
Communication protocols	4G, Wi-Fi, Ethernet
User authentication	OCPP 1.6J (Can be upgraded to OCPP 2.0.1 later) APP, RFID card, Credit card (Optional)

Software Update

OTA updates via web portal

Certification and Standards

Safety and compliance	IEC 61851-1; IEC 61851-23; IEC 61851-21-2; ISO 15118 CE,
Certification	EMC Class A, Eichrechtskonform (Optional)
Warranty	24 months, warranty extension possible

* All pictures shown are for illustration purpose only. Actual product and specifications may vary due to product enhancement



Phone: 0800 387877
E-mail: info@thundergrid.net
Website: thundergrid.net

Thundergrid

